NSN 5935-01-105-8413

Body Style:

Overall Length:

Test Data Document:

Straight shape, flange mount

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-105-8413

2.062 inches
Bushing Diameter:
1.328 inches
Overall Height:
1.437 inches
Environmental Protection:
Heat resistant and salt water resistant
Unthreaded Mounting Hole Diameter:
0.156 inches
Distance Between Mounting Facility Centers:
1.750 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
"3, 5-15" single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
15.0 single mating end all contact groupings
Contact Maximum Ac Voltage Rating In Volts:
125.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
125.0 single mating end all contact groupings
Polarization Method:
Contact
Shell Type:
Solid
Terminal Location:
Side single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Terminal Type:
Screw single mating end all contact groupings
Included Contact Quantity:
2 single mating end 2nd contact grouping
Included Contact Type:
U-pin single mating end 1st contact grouping

81348-w-c-596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental

and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5935-01-105-8413

Electrical Receptacle Connector - Page 2 of 2



Specification Data	Spe	ecifica	ition	Data:
--------------------	-----	---------	-------	-------

81348-w-c-596/140 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0