## NSN 5935-01-106-0722

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-106-0722

**Body Style:** 

Straight type

**Overall Length:** 

**6.750** inches

**Overall Height:** 

0.270 inches

**Environmental Protection:** 

Salt water resistant and shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

0.104 inches

**Distance Between Mounting Facility Centers:** 

6.486 inches

**Mating End Quantity:** 

4

**Contact Position Arrangement Style:** 

2 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:** 

Plastic polyamide single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:** 

Pin single mating end single contact grouping

**Contact Material Specification:** 

Qq-b-613, comp 2, 1/2 h federal specification single material response single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-20693, type 1 military specification single material response single mating end

**Included Contact Quantity:** 

120 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.120 gold grains, troy

## NSN 5935-01-106-0722

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.