NSN 5935-01-106-0744

Electrical Plug Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-106-0744

| view Online at https://aerobasegroup.com/hsh/5555-01-100-07-44 |
|--|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, internal coupling |
| Overall Length: |
| 1.420 inches |
| Overall Diameter: |
| 1.531 inches |
| Environmental Protection: |
| Moisture proof and salt water resistant and vibration proof |
| Threaded Device Type: |
| Back shell |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 41 number 20 single mating end |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet latch |
| Thread Length: |
| 0.290 inches |
| Thready Qty Per Inch (tpi): |
| 18 |
| Thread Size: |
| 1.188 inches |
| Shell Material: |
| Aluminum alloy 6061 |
| Shell Material Specification: |
| Qq-a-591, a380 federal specification single material response or qq-a-367, t6 federal specification single material response |
| Test Data Document: |
| 81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Designator: |
| Unef |
| Specification Data: |

96906-ms3476 government standard

NSN 5935-01-106-0744

Electrical Plug Connector Body - Page 2 of 2



| N/a | |
|-------------------|--|
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A039b0 | |

Mil-std (military Standard):

Mil-c-26482 spec.

Shelf Life: