

View Online at <https://aerobasegroup.com/nsn/5935-01-106-1708>

**Thread Class:**

2b and 2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.695 inches

**Environmental Protection:**

Shock proof and vibration proof

**Distance From Mounting Shoulder To Front Face:**

1.053 inches

**Mounting Facility Thickness:**

0.062 inches

**Threaded Device Type:**

Coupling facility and mounting bushing

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Sma 1st mating end

**Contact Removability:**

Nonremovable all mating ends all contact groupings

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling nut

**Thready Qty Per Inch (tpi):**

36 and 24

**Thread Size:**

0.250 inches and 0.625 inches

**Contact Material:**

Copper alloy all mating ends all contact groupings

**Contact Surface Treatment:**

Gold all mating ends all contact groupings

**Insert Material:**

Plastic polycarbonate all mating ends

**Shell Material:**

Steel

**Shell Surface Treatment:**

Passivate

**Bushing Accommodation Hole Shape:**

Round

**Included Contact Type:**

Coaxial socket 2nd mating end 2nd contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Uns and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0