NSN 5935-01-106-2396

Unable to decode and unable to decode

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-106-2396

| Body Style: |
|--|
| Straight shape |
| Overall Length: |
| 1.350 inches |
| Overall Height: |
| 0.495 inches |
| Overall Width: |
| 0.250 inches |
| Environmental Protection: |
| Humidity resistant and salt water resistant |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 10 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 5.0 single mating end single contact grouping |
| Contact Maximum Dc Voltage Rating In Volts: |
| 1000.0 single mating end single contact grouping |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Jackscrew-socket |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Beryllium single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Contact Surface Treatment Specification: |
| Mil-g-45204 military specification all treatment responses single mating end single contact grouping |
| Terminal Type: |
| Pin single mating end single contact grouping |
| Contact Material Specification: |
| Qq-c-530 federal specification single material response single mating end single contact grouping |
| Shell Material: |
| Plastic diallyl phthalate mineral filled |
| Shell Material Specification: |
| Mil-m-14 military specification single material response |
| Unable To Decode: |

NSN 5935-01-106-2396

Electrical Receptacle Connector - Page 2 of 2



| Included Contact Quantit | ty: |
|--------------------------|-----|
|--------------------------|-----|

10 single mating end single contact grouping

Special Features:

Jackscrew type-female and location-left handandjackscrew type-male and location-right hand

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.