Electrical Receptacle Connector - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-106-3909

| Overa | all Length: |
|--------|---|
| 2.875 | inches |
| Overa | all Height: |
| 1.375 | inches |
| Overa | all Width: |
| 1.375 | inches |
| Cente | er To Center Distance Between Mounting Facilities Parallel To Height: |
| 1.062 | inches |
| Dista | nce Between Centerlines Of Mounting Facilities Parallel To Body Width |
| 1.062 | inches |
| Dista | nce From Mounting Shoulder To Front Face: |
| 0.750 | inches |
| Matin | g End Quantity: |
| 1 | |
| Conta | act Removability: |
| Remo | vable single mating end single contact grouping |
| Conta | act Maximum Current Rating In Amps: |
| 41.0 s | single mating end single contact grouping |
| Polar | ization Method: |
| Keyw | ay or multiple keyway |
| Inser | Position In Deg: |
| 0.0 | |
| Shell | Туре: |
| Solid | |
| Term | inal Location: |
| Back | single mating end single contact grouping |
| Term | inal Type: |
| Solde | r well single mating end single contact grouping |
| Inclue | ded Contact Quantity: |
| 5 sing | le mating end single contact grouping |
| Inclue | ded Contact Type: |
| | d socket single mating end single contact grouping |
| Shelf | Life: |
| N/a | |
| Unit (| Of Measure: |
| | |
| Demi | litarization: |
| No | |
| Fiig: | |
| A039 | 00 |
| | d (military Standard): |
| | 5015 spec. |