Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-106-4529

Т	hread Class:
2	
т	hread Direction:
R	light-hand
	ody Style:
	traight shape, external coupling
	overall Length:
	etween 1.406 inches and 1.471 inches
C	overall Height:
	etween 0.929 inches and 0.945 inches
C	overall Width:
в	etween 0.929 inches and 0.945 inches
Е	nvironmental Protection:
	loisture proof and salt water resistant and shock proof and vibration proof
	Inthreaded Mounting Hole Diameter:
	etween 0.116 inches and 0.126 inches
С	center To Center Distance Between Mounting Facilities Parallel To Height:
	etween 0.714 inches and 0.724 inches
D	istance Between Centerlines Of Mounting Facilities Parallel To Body Width:
в	etween 0.714 inches and 0.724 inches
D	istance From Mounting Shoulder To Front Face:
в	etween 0.894 inches and 0.906 inches
т	hreaded Device Type:
В	ack shell
M	lating End Quantity:
1	
С	contact Position Arrangement Style:
1:	2-oct single mating end
С	contact Removability:
R	emovable single mating end single contact grouping
Ρ	olarization Method:
K	eyway or multiple keyway
Ir	nsert Position In Deg:
1	05.0 and 140.0 and 204.0 and 307.0
S	hell Type:
s	olid
С	connector Locking Method:
В	ayonet pin
т	hready Qty Per Inch (tpi):
2	8
т	hread Size:
0	.625 inches



Terminal Location:	
Back single mating end	single contact grouping
Contact Material:	
Copper alloy single mati	ng end single contact grouping
Contact Surface Treatr	nent:
Gold single mating end	ingle contact grouping
Contact Surface Treatr	nent Specification:
Mil-g-45204, type 1, cl 1	military specification single treatment response single mating end single contact grouping
Terminal Type:	
Crimp single mating end	single contact grouping
Shell Material:	
Aluminum alloy 6061	
Shell Surface Treatmer	it:
Cadmium	
Shell Surface Treatmen	at Specification:
	deral specification single treatment response
Shell Material Specifica	
-	cification single material response
Included Contact Quar	
12 single mating end sin	
Included Contact Type	
	end single contact grouping
Precious Material And	
Contact surfaces gold	
Precious Material And	Weight:
0.012 gold grains, troy	C C C C C C C C C C C C C C C C C C C
Precious Material:	
Gold	
Test Data Document:	
81349-mil-c-81511 spec	fication (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
-	ercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
	rmance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designa	
Un	
Specification Data:	
81349-mil-c-81511/21 g	overnment specification
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standa	rd):
	-