Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-106-4530

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
Between 1.406 inches and 1.471 inches
Overall Height:
Between 0.929 inches and 0.945 inches
Overall Width:
Between 0.929 inches and 0.945 inches
Environmental Protection:
Moisture proof and salt water resistant and shock proof and vibration proof
Unthreaded Mounting Hole Diameter:
Between 0.116 inches and 0.126 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.714 inches and 0.724 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.714 inches and 0.724 inches
Distance From Mounting Shoulder To Front Face:
Between 0.894 inches and 0.906 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
12-oct single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
118.0 and 176.0 and 219.0 and 309.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thready Qty Per Inch (tpi):
28
Thread Size:
0.625 inches

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:	
Back single mating er	nd single contact grouping
Contact Material:	
Copper alloy single m	nating end single contact grouping
Contact Surface Tre	atment:
Gold single mating er	nd single contact grouping
Contact Surface Tre	atment Specification:
Mil-g-45204, type 1,	cl 1 military specification single treatment response single mating end single contact grouping
Terminal Type:	
Crimp single mating e	and single contact grouping
Shell Material:	
Aluminum alloy 6061	
Shell Surface Treatr	nent:
Cadmium	
Shell Surface Treatr	nent Specification:
Qq-p-416, type 2, cl	3 federal specification single treatment response
Shell Material Speci	fication:
Qq-a-367, t6 federal s	specification single material response
Included Contact Qu	Jantity:
12 single mating end	single contact grouping
Included Contact Ty	pe:
Round pin single mat	ing end single contact grouping
Precious Material A	nd Location:
Contact surfaces gold	i de la constante de
Precious Material A	nd Weight:
0.012 gold grains, tro	y
Precious Material:	
Gold	
Test Data Document	
81349-mil-c-81511 sp	pecification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes con	nmercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and pe	rformance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Desig	nator:
Un	
Specification Data:	
81349-mil-c-81511/21	government specification
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Star	ndard):
<u></u>	