## NSN 5935-01-106-7358

Receptacle Dummy Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-106-7358 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** Between 0.760 inches and 0.800 inches **Overall Height:** 1.437 inches **Overall Width:** 1.437 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock proof and vibration proof **Unthreaded Mounting Hole Diameter:** Between 0.116 inches and 0.125 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.156 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.156 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 18 and 18 **Thread Size:** 1.188 inches and 1.312 inches **Insert Material:** Plastic epoxy single mating end **Shell Material:** Aluminum alloy **Shell Surface Treatment:** 

Nickel

**Shell Surface Treatment Specification:** 

Mil-c-26074 cl 3 or4, grade b military specification single treatment response

## NSN 5935-01-106-7358

Receptacle Dummy Connector - Page 2 of 2



Qq-a-367 federal specification single material response

**Thread Series Designator:** 

Unef and unef

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26074 spec.