

View Online at <https://aerobasegroup.com/nsn/5935-01-107-0864>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

2.630 inches

Overall Height:

0.780 inches

Overall Width:

0.440 inches

Distance Between Mounting Facility Centers:

2.320 inches

Threaded Device Type:

Mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

41 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

13.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Screw

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-p-19833, ty gdi-30 military specification single material response single mating end

Included Contact Quantity:

41 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.041 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.