Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-108-0692

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
Between 1.406 inches and 1.471 inches
Overall Height:
Between 1.335 inches and 1.351 inches
Overall Width:
Between 1.335 inches and 1.351 inches
Environmental Protection:
Moisture proof and salt water resistant and shock proof and vibration proof
Unthreaded Mounting Hole Diameter:
Between 0.116 inches and 0.126 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.057 inches and 1.067 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.057 inches and 1.067 inches
Distance From Mounting Shoulder To Front Face:
Between 0.894 inches and 0.906 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
18-21 f03 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thready Qty Per Inch (tpi):
28
Thread Size:
1.125 inches



erminal Location:	
ack single mating end single contact grouping	
ontact Material:	
opper alloy single mating end single contact grouping	
ontact Surface Treatment:	
old single mating end single contact grouping	
ontact Surface Treatment Specification:	
il-g-45204, type 1, cl 1 military specification single treatment response single mating end single contact gro	uping
erminal Type:	
imp single mating end single contact grouping	
nell Material:	
uminum alloy 6061	
nell Surface Treatment:	
admium	
nell Surface Treatment Specification:	
q-p-416, type 2, cl 3 federal specification single treatment response	
nell Material Specification:	
q-a-367, t6 federal specification single material response	
cluded Contact Quantity:	
single mating end single contact grouping	
cluded Contact Type:	
ound pin single mating end single contact grouping	
recious Material And Location:	
ontact surfaces gold	
recious Material And Weight:	
014 gold grains, troy	
recious Material:	
bld	
est Data Document:	
349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification	n type data in specification
rmat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting genera	I type data on certain
vironmental and performance requirements and test conditions that are shown as "typical", "average", "",	etc.).
nread Series Designator:	
ı	
pecification Data:	
349-mil-c-81511/21 government specification	
nelf Life:	
'a	
nit Of Measure:	
emilitarization:	
ig:	
- 039b0	
il-std (military Standard):	
<u> </u>	