Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-108-2560

2a Thread Direction: Right-hand Body Style: Straight shape, external coupling w/backshell Overall Length: 1.662 inches Overall Height: 1.625 inches Overall Width: 1.625 inches Durtreaded Mounting Hole Diameter: 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches Distance From Mounting Shoulder To Front Face: 0.750 inches Distance Trype:
Right-handBody Style:Straight shape, external coupling w/backshellOverall Length:1.662 inchesOverall Height:1.625 inchesOverall Width:1.625 inchesOverall Width:1.625 inchesOuthreaded Mounting Hole Diameter:0.120 inchesCenter To Center Distance Between Mounting Facilities Parallel To Height:1.250 inchesDistance Between Centerlines Of Mounting Facilities Parallel To Body Width:1.250 inchesDistance From Mounting Shoulder To Front Face:0.750 inches
Body Style:Straight shape, external coupling w/backshellOverall Length:1.662 inchesOverall Height:1.625 inchesOverall Width:1.625 inchesUnthreaded Mounting Hole Diameter:0.120 inchesCenter To Center Distance Between Mounting Facilities Parallel To Height:1.250 inchesDistance Between Centerlines Of Mounting Facilities Parallel To Body Width:1.250 inchesDistance From Mounting Shoulder To Front Face:0.750 inches
Straight shape, external coupling w/backshell Overall Length: 1.662 inches Overall Height: 1.625 inches Overall Width: 1.625 inches Unthreaded Mounting Hole Diameter: 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Widthe 1.250 inches Distance From Mounting Shoulder To Front Face: 0.750 inches
Overall Length:1.662 inchesOverall Height:1.625 inchesOverall Width:1.625 inchesUnthreaded Mounting Hole Diameter:0.120 inchesCenter To Center Distance Between Mounting Facilities Parallel To Height:1.250 inchesDistance Between Centerlines Of Mounting Facilities Parallel To Body Width:1.250 inchesDistance From Mounting Shoulder To Front Face:0.750 inches
1.662 inches Overall Height: 1.625 inches Overall Width: 1.625 inches Unthreaded Mounting Hole Diameter: 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Widthe 1.250 inches Distance From Mounting Shoulder To Front Face: 0.750 inches
Overall Height: 1.625 inches Overall Width: 1.625 inches Unthreaded Mounting Hole Diameter: 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches Distance From Mounting Shoulder To Front Face: 0.750 inches
1.625 inches Overall Width: 1.625 inches Unthreaded Mounting Hole Diameter: 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches Distance From Mounting Shoulder To Front Face: 0.750 inches
Overall Width: 1.625 inches Unthreaded Mounting Hole Diameter: 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches Distance From Mounting Shoulder To Front Face: 0.750 inches
 1.625 inches Unthreaded Mounting Hole Diameter: 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches Distance From Mounting Shoulder To Front Face: 0.750 inches
Unthreaded Mounting Hole Diameter: 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches Distance From Mounting Shoulder To Front Face: 0.750 inches
0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches Distance From Mounting Shoulder To Front Face: 0.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches Distance From Mounting Shoulder To Front Face: 0.750 inches
 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches Distance From Mounting Shoulder To Front Face: 0.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches Distance From Mounting Shoulder To Front Face: 0.750 inches
1.250 inches Distance From Mounting Shoulder To Front Face: 0.750 inches
Distance From Mounting Shoulder To Front Face: 0.750 inches
0.750 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
22-22 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
110.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thread Size:
1.375 inches
Terminal Location:
Back single mating end single contact grouping
Insert Material:
Plastic silicone single mating end



Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

4 single mating end single contact grouping

Test Data Document:

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-5015 spec.