

View Online at <https://aerobasegroup.com/nsn/5935-01-108-4240>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.433 inches

Distance From Mounting Shoulder To Front Face:

0.293 inches

Mounting Facility Thickness:

0.075 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Smc single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded coupling nut

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic fluorocarbon single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold and copper

Shell Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response and mil-c-14550 military specification 2nd treatment response

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round keyed

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact and shell surfaces gold

Precious Material And Weight:

0.105 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.