

View Online at <https://aerobasegroup.com/nsn/5935-01-108-5447>

Body Style:

Right angle type

Overall Length:

3.550 inches

Overall Width:

0.250 inches

Body Height:

0.335 inches

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

3.300 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

Guide Design And Location:

D shape socket right-hand at 9 o'clock

Insert Material Specification:

Mil-m-14 military specification single material response single mating end

Included Contact Quantity:

54 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.054 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.