

View Online at <https://aerobasegroup.com/nsn/5935-01-108-7591>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling w/backshell

Overall Length:

Between 0.927 inches and 0.947 inches

Overall Diameter:

Between 1.205 inches and 1.225 inches

Environmental Protection:

Moisture proof and salt water resistant and shock proof and vibration proof

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

14-37 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

90.0 and 145.0 and 195.0 and 252.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Thready Qty Per Inch (tpi):

28

Thread Size:

0.875 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 1 or 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy 6061

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074, cl 3, grade a military specification single treatment response

Shell Material Specification:

Qq-a-367, t6 federal specification single material response

Included Contact Quantity:

37 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.037 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Un

Specification Data:

81349-mil-c-81511/56 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.