## NSN 5935-01-108-8069

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-108-8069

**Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.406 inches **Overall Diameter:** 0.248 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 36 and 36 **Thread Size:** 0.250 inches and 0.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic polyamide single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:** Gold

Included Contact Quantity:

1 single mating end single contact grouping

## NSN 5935-01-108-8069

Electrical Receptacle Connector - Page 2 of 2



Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact and shell surfaces gold
Precious Material And Weight:
0.105 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Uns and uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0