# NSN 5935-01-109-2245

**Thread Class:** 

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-109-2245

2a
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
3.400 inches
Overall Height:
0.575 inches
Overall Width:
0.340 inches
Environmental Protection:
Moisture resistant
Distance Between Mounting Facility Centers:
2.600 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Tab, solder lug single mating end single contact grouping

# NSN 5935-01-109-2245

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Material Specification:**

Qq-b-750, comp a federal specification single material response single mating end single contact grouping

# **Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end

# **Included Contact Quantity:**

48 single mating end single contact grouping

# **Included Contact Type:**

Hermaphrodite single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.048 gold grains, troy

**Precious Material:** 

Gold

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.