NSN 5935-01-109-7535

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-109-7535 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.678 inches **Overall Height:** 0.500 inches **Overall Width:** 0.500 inches **Unthreaded Mounting Hole Diameter:** 0.102 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.340 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.340 inches **Distance From Mounting Shoulder To Front Face:** 0.310 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Sma single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 36 **Thread Size:** 0.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:**

Contact Surface Treatment:

Gold single mating end single contact grouping

Copper alloy single mating end single contact grouping

NSN 5935-01-109-7535

Electrical Receptacle Connector - Page 2 of 2



Insert	Mata	rial:
msert	wate	Hai.

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c, class 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Shell Material:

Steel

Shell Material Specification:

Qq-s-764, class 303, cond a federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.