Electrical Plug Connector - Page 1 of 2

<u>AeroBase</u>

View Online at https://aerobasegroup.com/nsn/5935-01-109-8459

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.234 inches
Overall Diameter:
0.984 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
4-nov single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
14.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Thread Length:
0.219 inches
Thready Qty Per Inch (tpi):
24
Thread Size:
0.562 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Solder well single moting and single context grouping

Solder well single mating end single contact grouping

# NSN 5935-01-109-8459

Electrical Plug Connector - Page 2 of 2



#### **Shell Material:**

Aluminum alloy

Shell Surface Treatment:

Cadmium

## Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

## **Included Contact Quantity:**

4 single mating end single contact grouping

#### Included Contact Type:

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

#### **Precious Material And Weight:**

0.020 gold grains, troy and 0.020 silver grains, troy

#### Precious Material:

Gold and silver

#### **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unef

Specification Data: 96906-ms27467 government standard Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A039b0

## Mil-std (military Standard):

Mil-c-38999 spec.