

View Online at <https://aerobasegroup.com/nsn/5935-01-109-8953>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

3.564 inches

Overall Height:

Between 2.355 inches and 2.396 inches

Overall Width:

Between 2.355 inches and 2.396 inches

Environmental Protection:

Thermal shock resistant and moisture resistant and salt water resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.177 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.844 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.844 inches

Distance From Mounting Shoulder To Front Face:

Between 2.204 inches and 3.564 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

28-3 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

73.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1250.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

1750.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

345.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

0.531 inches

Thready Qty Per Inch (tpi):

10

Thread Size:

2.000 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and nickel

Shell Surface Treatment Specification:

Qq-p-416, type 2 federal specification 1st treatment response and qq-n-290 federal specification 2nd treatment response

Included Contact Quantity:

3 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.015 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-22992 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Double stub

Specification Data:

96906-ms90555 government standard

Shelf Life:

Nil

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.