## NSN 5935-01-110-3250

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-110-3250

Body Style:
Straight type
Overall Length:
2.530 inches
Overall Height:
0.745 inches
Overall Width:
0.360 inches
Unthreaded Mounting Hole Diameter:
0.096 inches
Distance Between Mounting Facility Centers:
2.300 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
1.0 single mating end single contact grouping
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Glass single mating end and plastic polyester single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290 federa
specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-b-750, comp a federal specification single material response single mating end single contact grouping
Incort Material Specification:

Mil-m-24519, type gpt-30f military specification single material response single mating end

### **Included Contact Quantity:**

34 single mating end single contact grouping

### **Included Contact Type:**

Round pin single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold

# NSN 5935-01-110-3250

Electrical Receptacle Connector - Page 2 of 2



<b>Precious Material And Weight:</b>
0.034 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.