# NSN 5935-01-110-3260

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-110-3260  $\,$ 

Thread Class:
2a and 2b
Thread Direction:
Right-hand
Body Style:
Straight type
Overall Length:
4.150 inches
Overall Height:
0.465 inches
Overall Width:
0.250 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
3.900 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:

Plastic diallyl phthalate single mating end

## NSN 5935-01-110-3260

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Solder well single mating end single contact grouping

#### **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

#### **Insert Material Specification:**

Mil-m-14 military specification single material response single mating end

#### **Unable To Decode:**

Unable to decode and unable to decode

#### **Included Contact Quantity:**

66 single mating end single contact grouping

#### **Included Contact Type:**

Round socket single mating end single contact grouping

#### **Special Features:**

Jackscrew type-male and location-left handandjackscrew type-female and location-right hand

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.066 gold grains, troy

#### **Precious Material:**

Gold

#### **Thread Series Designator:**

Unc

## Shelf Life:

N/a

#### **Unit Of Measure:**

--

## Demilitarization:

No

## Fiig:

A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.