

View Online at <https://aerobasegroup.com/nsn/5935-01-110-7040>

**Body Style:**

Straight shape

**Overall Length:**

Between 0.160 inches and 0.180 inches

**Overall Height:**

Between 0.315 inches and 0.445 inches

**Overall Width:**

Between 0.065 inches and 0.080 inches

**Environmental Protection:**

Vibration resistant and shock resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

1 row of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

250.0 single mating end single contact grouping

**Connector Cable Strain Relief Method:**

Potting type and shrinkable tubing

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and copper alloy single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-c-45204, type 2, cl 1 military specification all treatment responses single mating end single contact grouping

**Insert Material Specification:**

Mil-m-19887, type 610 military specification single material response single mating end

**Included Contact Quantity:**

3 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.003 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-45204 spec.