

View Online at <https://aerobasegroup.com/nsn/5935-01-110-7040>

Body Style:

Straight shape

Overall Length:

Between 0.160 inches and 0.180 inches

Overall Height:

Between 0.315 inches and 0.445 inches

Overall Width:

Between 0.065 inches and 0.080 inches

Environmental Protection:

Vibration resistant and shock resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

1 row of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end single contact grouping

Connector Cable Strain Relief Method:

Potting type and shrinkable tubing

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper alloy single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-c-45204, type 2, cl 1 military specification all treatment responses single mating end single contact grouping

Insert Material Specification:

Mil-m-19887, type 610 military specification single material response single mating end

Included Contact Quantity:

3 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.003 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-45204 spec.