Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-110-7942

# Thread Class:

2a and 2b

#### **Thread Direction:**

Left-hand and right-hand

### Body Style:

Straight shape, internal coupling

#### **Overall Length:**

1.797 inches

#### **Overall Diameter:**

1.806 inches

#### **Environmental Protection:**

Corrosion resistant and vibration resistant and shock resistant and explosion proof

#### Threaded Device Type:

Back shell and coupling facility

#### Mating End Quantity:

1

# Contact Position Arrangement Style:

24-11 single mating end

# **Contact Removability:**

Nonremovable single mating end all contact groupings

#### **Contact Maximum Current Rating In Amps:**

73.0 single mating end 1st contact grouping

#### Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end all contact groupings

#### Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end all contact groupings

#### **Polarization Method:**

Key, multiple key groove

#### Insert Position In Deg:

0.0

#### Shell Type:

Solid

# Connector Locking Method:

Internally threaded coupling ring

# Thread Length:

0.594 inches

# Thready Qty Per Inch (tpi):

18 and 10

# Thread Size:

1.375 inches and 1.500 inches

#### **Terminal Location:**

Back single mating end all contact groupings

# NSN 5935-01-110-7942 Electrical Plug Connector - Page 2 of 2



Contact Mater	ial:
Copper alloy si	ngle mating end all contact groupings
Contact Surfa	ce Treatment:
Silver single ma	ating end all contact groupings
Insert Material	:
Rubber single r	mating end
Contact Surfa	ce Treatment Specification:
Qq-s-365 feder	al specification single treatment response single mating end all contact groupings
Terminal Type	::
Solder well sing	gle mating end all contact groupings
Shell Material:	
Aluminum alloy	,
Shell Surface	Treatment:
Anodize	
Included Cont	act Quantity:
6 single mating	end 2nd contact grouping
Included Cont	act Type:
Round pin sing	le mating end all contact groupings
Precious Mate	rial And Location:
Contact surface	es silver
Precious Mate	rial And Weight:
0.045 silver gra	ins, troy
Precious Mate	rial:
Silver	
Thread Series	Designator:
Unef and doub	le stub
Shelf Life:	
N/a	
Unit Of Measu	re:
Demilitarizatio	n:
No	
Fiig:	