Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-111-0683

# Thread Class:

2a

**Thread Direction:** 

Right-hand

### **Body Style:**

Straight shape, external coupling

### **Overall Length:**

1.275 inches

### **Overall Height:**

1.578 inches

### **Overall Width:**

1.578 inches

### **Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

### **Unthreaded Mounting Hole Diameter:**

0.120 inches

### Center To Center Distance Between Mounting Facilities Parallel To Height:

1.250 inches

### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

# Distance From Mounting Shoulder To Front Face:

Between 0.556 inches and 0.587 inches

### **Threaded Device Type:**

Back shell

### Mating End Quantity:

1

### **Contact Position Arrangement Style:**

22-21 single mating end

### **Contact Removability:**

Removable single mating end single contact grouping

### Contact Maximum Ac Voltage Rating In Volts:

1000.0 single mating end single contact grouping

### **Polarization Method:**

Keyway or multiple keyway

### **Insert Position In Deg:**

135.0

Shell Type:

Solid

### **Connector Locking Method:**

Bayonet pin

### Thready Qty Per Inch (tpi):

18

# NSN 5935-01-111-0683

Electrical Receptacle Connector - Page 2 of 2



# Thread Size:

1.312 inches

### **Terminal Location:**

Back single mating end single contact grouping

# Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

# **Contact Surface Treatment Specification:**

Mil-g-45204, type 1, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290,

grade e federal specification 2nd treatment response single mating end single contact grouping

### **Terminal Type:**

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074, cl 3, grade b military specification single treatment response

### **Included Contact Quantity:**

21 single mating end single contact grouping

### Included Contact Type:

Round pin single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold

### **Precious Material And Weight:**

0.021 gold grains, troy

### **Precious Material:**

Gold

### **Test Data Document:**

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Thread Series Designator:**

Unef

### **Specification Data:**

96906-ms3470 government standard

#### Shelf Life:

N/a

### Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.