

View Online at <https://aerobasegroup.com/nsn/5935-01-111-3585>

**Thread Class:**

2b and 2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external/internal coupling

**Overall Length:**

1.250 inches

**Overall Diameter:**

0.830 inches

**Environmental Protection:**

Shock proof and vibration proof

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Sma 2nd mating end

**Contact Removability:**

Nonremovable all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling ring and externally threaded shell

**Thready Qty Per Inch (tpi):**

24 and 36

**Thread Size:**

0.625 inches and 0.250 inches

**Contact Surface Treatment:**

Gold all mating ends single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 2 military specification single treatment response all mating ends single contact grouping

**Shell Material:**

Stainless steel

**Shell Surface Treatment:**

Passivate

**Included Contact Quantity:**

1 2nd mating end single contact grouping

**Included Contact Type:**

Coaxial socket 2nd mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unef and uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.