## NSN 5935-01-111-4578

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-111-4578 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, rectangular **Overall Length:** 2.593 inches **Overall Height:** 0.686 inches **Overall Width:** 1.312 inches **Environmental Protection:** Thermal shock resistant and vibration resistant and humidity resistant and corrosion resistant **Unthreaded Mounting Hole Diameter:** 0.093 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.410 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.125 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 8.5 single mating end single contact grouping **Connector Locking Method:** Screw Thready Qty Per Inch (tpi): **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end

## NSN 5935-01-111-4578

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, gr d, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

#### **Terminal Type:**

Crimp single mating end single contact grouping

#### **Contact Material Specification:**

Qq-b-750 federal specification single material response single mating end single contact grouping

#### **Insert Material Specification:**

Mil-m-14, type sdq-f or gdi-30f military specification single material response single mating end

#### **Included Contact Quantity:**

20 single mating end single contact grouping

#### **Included Contact Type:**

Hermaphrodite single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.020 gold grains, troy

#### **Precious Material:**

Gold

#### **Test Data Document:**

81349-mil-c-28731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Thread Series Designator:**

Unc

#### **Specification Data:**

81349-mil-c-28731/9 government specification

#### Shelf Life:

N/a

### Unit Of Measure:

--

#### **Demilitarization:**

No

# Fiig:

A039b0

#### Mil-std (military Standard):

Mil-g-45204 spec.