

View Online at <https://aerobasegroup.com/nsn/5935-01-111-5567>

**Body Style:**

Right angle type

**Overall Length:**

3.540 inches

**Overall Height:**

0.330 inches

**Environmental Protection:**

Vibration resistant and shock resistant and humidity resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.075 inches and 0.078 inches

**Distance Between Mounting Facility Centers:**

3.340 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Polarization Method:**

Guide pin/socket

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic polyamide single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Contact Material Specification:**

Qq-b-613, comp 2 1/2 hard federal specification single material response single mating end single contact grouping

**Guide Design And Location:**

D shape pin right-hand at 9 o'clock

**Shell Material:**

Aluminum alloy 6063 or aluminum alloy 6061

**Shell Surface Treatment:**

Gold and chromate

**Shell Surface Treatment Specification:**

Mil-c-5541 military specification all treatment responses

**Shell Material Specification:**

Qq-a-200/9, t6 federal specification single material response or qq-a-200/8, t6 federal specification single material response

**Insert Material Specification:**

L-p-410 federal specification single material response single mating end or mil-m-20693, type 1 military specification single material response single mating end

**Included Contact Quantity:**

60 single mating end single contact grouping

**Included Contact Type:**

Flat pin single mating end single contact grouping

**Precious Material And Location:**

Contact and shellsurfaces gold

**Precious Material And Weight:**

0.160 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.