

View Online at <https://aerobasegroup.com/nsn/5935-01-111-5567>

Body Style:

Right angle type

Overall Length:

3.540 inches

Overall Height:

0.330 inches

Environmental Protection:

Vibration resistant and shock resistant and humidity resistant

Unthreaded Mounting Hole Diameter:

Between 0.075 inches and 0.078 inches

Distance Between Mounting Facility Centers:

3.340 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Guide pin/socket

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Contact Material Specification:

Qq-b-613, comp 2 1/2 hard federal specification single material response single mating end single contact grouping

Guide Design And Location:

D shape pin right-hand at 9 o'clock

Shell Material:

Aluminum alloy 6063 or aluminum alloy 6061

Shell Surface Treatment:

Gold and chromate

Shell Surface Treatment Specification:

Mil-c-5541 military specification all treatment responses

Shell Material Specification:

Qq-a-200/9, t6 federal specification single material response or qq-a-200/8, t6 federal specification single material response

Insert Material Specification:

L-p-410 federal specification single material response single mating end or mil-m-20693, type 1 military specification single material response single mating end

Included Contact Quantity:

60 single mating end single contact grouping

Included Contact Type:

Flat pin single mating end single contact grouping

Precious Material And Location:

Contact and shellsurfaces gold

Precious Material And Weight:

0.160 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.