

View Online at <https://aerobasegroup.com/nsn/5935-01-111-7603>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.230 inches

**Overall Diameter:**

1.531 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

**Threaded Device Type:**

Back shell

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

20-39 single mating end

**Contact Removability:**

Removable single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

1000.0 single mating end all contact groupings

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

63.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.188 inches

**Terminal Location:**

Back single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings and nickel single mating end all contact groupings

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, cl 1, grade c military specification 1st treatment response single mating end all contact groupings and qq-n-290, grade e federal specification 2nd treatment response single mating end all contact groupings

**Terminal Type:**

Crimp single mating end all contact groupings

**Shell Material:**

Aluminum alloy 6061

**Shell Surface Treatment:**

Nickel

**Shell Surface Treatment Specification:**

Mil-c-26074, cl 3, grade b military specification single treatment response

**Shell Material Specification:**

Qq-a-367 federal specification single material response

**Included Contact Quantity:**

37 single mating end 2nd contact grouping

**Included Contact Type:**

Round socket single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.047 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef

**Specification Data:**

96906-ms3475 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.