NSN 5935-01-111-7634

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-111-7634 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.405 inches **Overall Height:** 1.453 inches **Overall Width:** 1.453 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Unthreaded Mounting Hole Diameter:** 0.150 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.125 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.125 inches **Distance From Mounting Shoulder To Front Face:** Between 0.462 inches and 0.493 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 16-26 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1000.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 275.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin

20

Thready Qty Per Inch (tpi):

NSN 5935-01-111-7634

Electrical Receptacle Connector - Page 2 of 2



| Thread Size: |
|--|
| 1.000 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping |
| Contact Surface Treatment Specification: |
| Mil-g-45204 type 1, class 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290 |
| grade e federal specification 2nd treatment response single mating end single contact grouping |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy 6061 |
| Shell Surface Treatment: |
| Nickel |
| Shell Surface Treatment Specification: |
| Mil-c-26074 class 3, grade b military specification single treatment response |
| Shell Material Specification: |
| Qq-a-367, t6 federal specification single material response |
| Included Contact Quantity: |
| 26 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.026 gold grains, troy |
| Precious Material: |
| Gold |
| Test Data Document: |
| 81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Designator: |
| Unef |
| Specification Data: |
| 96906-ms3472 government standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

A039b0

Demilitarization:

No **Fiig:**