Electrical Connector Cover - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-111-7726

2b Chrediolicetion: Sigh-hand Eyo halde Diameter: 2 Hindsholtems: Body Height: Body Height: Overall Diameter: 2 Tyl inches Brackment Festure Length: Body Delight Signature: 2 Tyl inches Brackment Festure Length: Body Delight Signature: 2 Tyl inches Brackment Festure Length: Body Delight Signature: 2 Tyl inches Brackment Festure Length: Body Delight Signature: 2 Tyl inches Brackment Festure Length: 2 Stor Designature: 2 Stor Designature: 2 Stor De	Thread Class:	
Righthand Eye Inside Diameter: 2841 Inchas Furnished Items: Link chain Body Height: 0.300 Inchas Overall Diameter: 2.719 Inchas Attachment Feature Length: 0.000 Inchas Size Designation: 284 10 11 Inteaded Capation: 284 12 Inteaded Capation: 286 280 Designation: 281 11 Inteaded Capation: 281 282 Designation: 284 12 Inteaded Capation: 280 280 Inteade Size 280 Inchas Material: Aurnium alloy Sadiancia Aurnium alloy Sadiancia	2b	
P Index 2.641 indexs Puriable lames: Link chain Body Height: 0.380 indexs Overall Diameter: 2.719 indexs Attachment Feature Length: 6.000 indexs Size Designation: 6.000 indexs Monting Facility Type And Quantity: 1 threaded coupling Thread State: 2.500 indexs 2.500 indexs Monting Facility Type And Quantity: 1 threaded coupling Thread State: 2.500 indexs Material: Aurinum alloy Material: Aurinum alloy State Treatment: Cadmium and nickel Style Designator: External threads wichain or rope Style Designator: Cadmium and nickel Style Designator: Store Designator: Cadmium and nickel State Treatment: Cadmium and nickel State Treatment: Cadmium and nickel State Treatthreat: C	Thread Direction:	
2441 inches Furnished Items: Link chain Body Height: 0.360 inches Overall Diameter: 2.718 inches Attachment Feature Length: 0.000 inches 5000 inches 5000 inches 5000 inches 5000 inches 5120 Designation: 301 10 Thready Cuty Per Inch (pt): 10 Thready Cuty Per Inch (pt): 2.500 inches Absorbal: 2.500 inches Material: Auminum alloy Material: Cutrace Treatment: Cadmium an inckel Strikee Treatment: Cadmium an inckel <	Right-hand	
Fursished Items: Link chain Body Hight: 3800 Inches Overall Diameter: 2.719 Inches Attachmet Feature Length: 3000 Inches Stez Designation: 300 301 Threads Oklameter 1000 Inches Stez Designation: 300 1000 Inches Threads Oklameter 1000 Inches 1000 Inches Stez Designation: 300 1000 Inches 2.500 Inches 1000 Inches 2.600 Inches Aumium alloy 1000 Inches Sufface Treatment: Cadmium and Inckel Sufface Treatment:	Eye Inside Diame	ter:
Link chain Body Height: 0.380 inches Overall Diameter: 2.719 inches Attachment Feature Length: 6.000 inches Size Designation: 30 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 10 Stool inches Advertial: Auroin maloy Matterial: Auroin not inckel Style Designator: Cadmium and inckel Style Designator: Style Designator:<	2.641 inches	
Body Height: 0.380 inches Overall Diameter: 0.710 inches 2.710 inches 0.00 inches Stace Designation: 0.00 inches Size Designation: 0.00 inches 10 10 Mouting Facility Type And Quantity: 10 10 10 Thready Guy Per Inch (tp): 10 10 10 Autorium alloy 10 Autorium alloy 10 Autorium alloy 10 Stories Treatment: 10 Cadmium and inckel 10 Strikes Wichain or rope 10 Strikes Treatment: 10 Cadmium and nickel 10 Strikes Treatment: 10 Cadmium and nickel 10 Strikes Wichain or rope 10 Strikes Stri	Furnished Items:	
0.900 inches Cverall Diameter: 2.719 inches 2.719 inches Attachment Feature Length: 4.000 inches Coutometers Couto	Link chain	
Overall Diameter: 2.719 inches Attachment Feature Length: 6.000 inches Size Designation: 30 Size Designation: 30 Monting Facility Type And Quantity: 1 1 threaded coupling 1 Thready Qty Per Inch (tpl): 1 10 1 Thread Size: 2 2.500 inches 1 Material: 1 Aluminum alloy 1 Atterial: 1 Aluminum alloy 1 Surface Treatment: 1 Cadmium and nickel 1 Style Designator: 1 Rest Pace Treatment: 1 Cadmium and nickel 1 Style Designator: 1 Stafface Treatment: 1 Cadmium and nickel 1 Style Designator: 1 Stafface Treatment: 1 Caddium and nickel 1 Style Designator: 1 Stafface Treatment: 1 Caddium and nickel 1 Style Designator: 1	Body Height:	
219 inches Attachment Feature Length: 6.000 inches Size Designation: 30 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 10 Thread Size: 2.500 inches Material: Atterial: Stafe Treatment: Cadmium and inckel Stafe Treatment: Cadmium an inckel	0.980 inches	
Attachment Feature Length: 6.000 inches Size Designation: 36 Moning Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 10 Thread Size: 2.500 inches Matrial: Aluminum alloy Material: Aluminum alloy Strikee Treatment: Cadmium and nickel Strikee Treatment: Strikee Treatment: Cadmium and nickel Strike Treatment: Strike Strike Strike Strike Strike Strike Strike Str	Overall Diameter:	
6.000 inches Size Designation: 36 Mouning Facility Type And Quantity: 1 threaded coupling Thready Cty Per Inch (tpi): 10 Thread Size: 2.500 inches Material: Aluminum alloy Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: External threads wichain or rope Surface Treatment: Cadmium and nickel Style Designator: External threads wichain or rope Surface Treatment: Cadmium and nickel Style Designator: External threads wichain or rope Surface Treatment: Cadmium and nickel Style Designator: External threads wichain or rope Surface Treatment: Cadmium and nickel Style Designator: Style Designator: Style Designator: Style Designator: Style Designator: Style Designator: Style Designator Style D	2.719 inches	
Size Designation: 36 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qy Per Inch (tpi): 10 Thready Qy Per Inch (tpi): 10 Thread Size: 32.00 inches Material: Aluminum alloy Material: Aluminum alloy Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Style Designator: Cadmium and nickel Style Designator: Style Designator: Cadmium and nickel Style Designator: Style Designator: Cadmium and nickel Style Designator: Style Desig	Attachment Featu	re Length:
36 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 10 Thread Size: 2.500 inches Material: Aluminum alloy Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: External threads w/chain or rope Surface Treatment: Cadmium and nickel Style Designator: External threads w/chain or rope Surface Treatment: Cadmium and nickel Test Data Document: B1349-mil-o-22992 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain cavitronmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Thread Series Designator: Ebulletistion Bouble stub Specification Instandard Specification Data: Specification Data:	6.000 inches	
Nounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 10 Thread Size: 2.500 inches Material: Aluminum alloy Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: External threads w/chain or rope Surface Treatment: Cadmium and nickel Test Data Document: 81349-mil-c-22992 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (inc	Size Designation:	
1 thread coupling Thread Yoy Per Inch (tpi): 10 Thread Size: 2.500 inches Material: Autoriant Aluminum alloy Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Style Designator: Starta Understand Style Sty	36	
Thready Qty Per Inch (tpi): 10 Thread Size: 2.500 inches Material: Aluminum alloy Material: Aluminum alloy Sufface Treatment: Cadmium and nickel Style Designator: Style Designator: Cadmium and nickel Style Document: Cadmium and nickel Style Document: Style Document: Cadmium and nickel Style Document: Style Document: Cadmium and nickel Duble scub Style Documential and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Thread Series Designator: Double stub Specification Data: Boso06-mst7349 government standard Shif Life: Na	Mounting Facility	Type And Quantity:
10 Thread Size: 2.500 inches Matrial: Aluminum alloy Matrial: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: External threads w/chain or rope Surface Treatment: Cadmium and nickel Test Data Document: 81349-mil-c-22992 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificatin type data in specificatin type data in sp	1 threaded couplin	g
Thread Size: 2.500 inches Aterial: Auminum alloy Aterial: Auminum alloy Material: Auminum alloy Surface Treatment: Cadmium and nickel Style Designator: External threads w/chain or rope Surface Treatment: Cadmium and nickel Style Designator: External threads w/chain or rope Surface Treatment: Cadmium and nickel Style Designator: External threads w/chain or rope Surface Treatment: Cadmium and nickel Test Data Document: External threads surface and threads on certain threads on certain threads commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain thread Series Designator: Invisonmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: External thread Series Designator: Double stub Specification Data: Besode-ms17349 government standard Sheff Life: Na Na	Thready Qty Per I	nch (tpi):
2.500 inches Material: Aluminum alloy Material: Aluminum alloy Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: External threads w/chain or rope Surface Treatment: Cadmium and nickel Test Data Document: 81349-mil-c-22992 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Double stub Specification Data: 96906-ms17349 government standard Sheff Life: Na	10	
Material: Aluminum alloy Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: External threads wichain or rope Surface Treatment: Cadmium and nickel Style Designator: Cadmium and nickel Starface Treatment: Cadmium and nickel Test Data Document: Ritya9-mil-c-22992 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Thread Series Designator: Double stub Specification Data: 96906-ms17349 government standard Sheff Life: N/a	Thread Size:	
Aluminum alloy Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: External threads w/chain or rope Surface Treatment: Cadmium and nickel Test Data Document: Risker value scommercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Pouble stub Specification Data: 99006-ms17349 government standard Sheff Life: Na	2.500 inches	
Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: External threads w/chain or rope Surface Treatment: Cadmium and nickel Cadmium and nickel Test Data Document: 81349-mil-c-22992 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Double stub Specification Data: 96906-ms17349 government standard Sheff Life: N/a	Material:	
Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: External threads w/chain or rope Surface Treatment: Cadmium and nickel Sturface Treatment: Cadmium and nickel Test Data Document: 81349-mil-c-22992 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Double stub Specification Data: 96906-ms17349 government standard Shelf Life: N/a	Aluminum alloy	
Surface Treatment: Cadmium and nickel Style Designator: External threads w/chain or rope Surface Treatment: Cadmium and nickel Test Data Document: 81349-mil-c-22992 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Double stub Specification Data: 96906-ms17349 government standard Shelf Life: N/a	Material:	
Cadmium and nickel Style Designator: External threads w/chain or rope Surface Treatment: Cadmium and nickel Test Data Document: 81349-mil-c-22992 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Double stub Specification Data: 96906-ms17349 government standard Shelf Life: N/a	Aluminum alloy	
Style Designator: External threads w/chain or rope Surface Treatment: Cadmium and nickel Test Data Document: 81349-mil-c-22992 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Double stub Specification Data: 96906-ms17349 government standard Shelf Life: N/a	Surface Treatmer	t:
External threads w/chain or rope Surface Treatment: Cadmium and nickel Test Data Document: 81349-mil-c-22992 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Double stub Specification Data: 96906-ms17349 government standard Shelf Life: N/a	Cadmium and nick	el
Surface Treatment: Cadmium and nickel Test Data Document: 81349-mil-c-22992 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Double stub Specification Data: 96906-ms17349 government standard Shelf Life: N/a	Style Designator:	
Cadmium and nickel Test Data Document: 81349-mil-c-22992 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Double stub Specification Data: 96906-ms17349 government standard Shelf Life: N/a	External threads w	/chain or rope
Test Data Document: 81349-mil-c-22992 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Double stub Specification Data: 96906-ms17349 government standard Shelf Life: N/a	Surface Treatmer	t:
81349-mil-c-22992 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Double stub Specification Data: 96906-ms17349 government standard Shelf Life: N/a	Cadmium and nick	el
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Double stub Specification Data: 96906-ms17349 government standard Shelf Life: N/a	Test Data Docum	ent:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Double stub Specification Data: 96906-ms17349 government standard Shelf Life: N/a	81349-mil-c-22992	specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Thread Series Designator: Double stub Specification Data: 96906-ms17349 government standard Shelf Life: N/a	format; excludes of	ommercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Double stub Specification Data: 96906-ms17349 government standard Shelf Life: N/a	environmental and	performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data: 96906-ms17349 government standard Shelf Life: N/a	Thread Series De	signator:
96906-ms17349 government standard Shelf Life: N/a	Double stub	
Shelf Life: N/a	Specification Data	à:
N/a	96906-ms17349 go	overnment standard
	Shelf Life:	
Unit Of Measure:	N/a	
	Unit Of Measure:	

NSN 5935-01-111-7726

Electrical Connector Cover - Page 2 of 2



Demilitarization:

No

Fiig:

A10100

Mil-std (military Standard):

Mil-c-22992 spec.