Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-112-5441

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.025 inches

Overall Width:

0.688 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Bnc single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

10000.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Spring friction

Radio Frequency Type Contact Characteristic Impedance In Ohms:

75.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

28

Thread Size:

0.500 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic fluorocarbon single mating end

Terminal Type:

Pin single mating end single contact grouping

NSN 5935-01-112-5441

Electrical Receptacle Connector - Page 2 of 2



Copper alloy	
	nteet Quentitu
	ntact Quantity:
-	ng end single contact grouping
3ushing Acc	commodation Hole Shape:
Round	
ncluded Co	ntact Type:
Coaxial sock	et single mating end single contact grouping
Precious Ma	terial And Location:
Contact surfa	ices silver
Precious Ma	terial And Weight:
0.005 silver g	jrains, troy
Precious Ma	terial:
Silver	
Thread Serie	es Designator:
Jnef	
Shelf Life:	
N/a	
Unit Of Meas	sure:
-	
Demilitarizat	ion:
No	
Fiig:	
A039b0	