NSN 5935-01-112-5460

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-112-5460

Body Style:

Straight edge type w/card guide

Overall Length:

4.392 inches

Overall Width:

Between 0.380 inches and 0.392 inches

Body Height:

Between 0.640 inches and 0.646 inches

Board Accommodated Width:

Between 0.054 inches and 0.071 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping and nickel alloy single mating end single contact grouping and zinc alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyester single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c or d military specification 1st treatment response single mating end single contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-c-586 federal specification all material responses single mating end single contact grouping

Insert Material Specification:

Mil-m-24519, type gpt-30f military specification single material response single mating end

Included Contact Quantity:

44 single mating end single contact grouping

Included Contact Type:

Leaf spring single mating end single contact grouping

NSN 5935-01-112-5460

Electrical Receptacle Connector - Page 2 of 2



Special Features:
Ground bushing at terminals no. 22, 24 and 44
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.044 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.