NSN 5935-01-112-7994

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-112-7994 **Body Style:** Straight shape, flush mount **Overall Length:** 1.109 inches **Overall Height:** 3.375 inches **Overall Width:** 3.937 inches **Unthreaded Mounting Hole Diameter:** 0.182 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 2.875 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 3.000 inches **Distance From Mounting Shoulder To Front Face:** 0.062 inches **Mating End Quantity:** 2 **Contact Position Arrangement Style:** 10 all mating ends **Contact Removability:** Nonremovable all mating ends all contact groupings **Contact Maximum Current Rating In Amps:** 20.0 all mating ends 2nd contact grouping Shell Type: Solid **Terminal Location:** Back all mating ends all contact groupings **Contact Material:** Copper alloy all mating ends all contact groupings **Contact Surface Treatment:** Gold all mating ends all contact groupings and nickel all mating ends all contact groupings **Insert Material:** Plastic diallyl phthalate all mating ends **Contact Surface Treatment Specification:** Mil-g-45204 military specification all treatment responses all mating ends all contact groupings **Terminal Type:** Solder well all mating ends all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

NSN 5935-01-112-7994

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification all treatment responses

Shell Material Specification:

Qq-a-591/a380 federal specification single material response

Insert Material Specification:

Mil-m-14, type mdg military specification single material response all mating ends

Included Contact Type:

Round pin all mating ends all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.