

View Online at <https://aerobasegroup.com/nsn/5935-01-113-2757>

Body Style:

Straight shape, internal coupling

Overall Length:

Between 1.470 inches and 1.530 inches

Overall Diameter:

0.800 inches

Environmental Protection:

Corrosion resistant and moisture resistant and vibration resistant

Cable Entrance Diameter:

0.110 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

N single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Rubber silicone class q single mating end

Contact Surface Treatment Specification:

Qq-s-365, ty ii grade a federal specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-b-626, 1/2 hard, comp 22 federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver and copper

Shell Surface Treatment Specification:

Qq-s-365, ty ii grade a federal specification 1st treatment response and mil-c-14550 military specification 2nd treatment response

Shell Material Specification:

Qq-b-626, 1/2 hard, comp 22 federal specification single material response

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact and body surfaces silver

Precious Material And Weight:

0.001 silver grains, troy

Precious Material:

Silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-14550 spec.