

View Online at <https://aerobasegroup.com/nsn/5935-01-113-2942>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight edge type w/mounting flange

Overall Length:

2.375 inches

Overall Height:

0.437 inches

Overall Width:

0.330 inches

Distance Between Mounting Facility Centers:

2.075 inches

Board Accommodated Length:

1.607 inches single board

Threaded Device Type:

Mounting stud

Board Accommodated Width:

Between 0.071 inches and 0.540 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

600.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-14 military specification single material response single mating end

Included Contact Quantity:

30 single mating end single contact grouping

Included Contact Type:

Hermaphrodite single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.030 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.