

View Online at <https://aerobasegroup.com/nsn/5935-01-113-5910>

**Thread Direction:**

Right-hand

**Body Style:**

Right angle type

**Overall Length:**

5.716 inches

**Overall Height:**

0.669 inches

**Overall Width:**

0.275 inches

**Environmental Protection:**

Humidity resistant and vibration resistant and shock resistant

**Distance Between Mounting Facility Centers:**

5.400 inches

**Threaded Device Type:**

Mounting stud

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Polarization Method:**

Guide pin/socket

**Connector Locking Method:**

Friction

**Thread Size:**

2.5 millimeters

**Thread Pitch In Millimeters:**

0.45

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Pin single mating end single contact grouping

**Contact Material Specification:**

Qq-b-626 military specification single material response single mating end single contact grouping or qq-c-530 military specification single material response single mating end single contact grouping

**Guide Design And Location:**

Hexagon shape female post left-hand at 12 oclock and hexagon shape female post right-hand at 12 oclock

**Insert Material Specification:**

Mil-m-14, type sdg-f or mil-p-19833, type gd1-30f military specification single material response single mating end

**Thread Tolerance Class:**

6g external

**Included Contact Quantity:**

66 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.096 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Iso s

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

spec.