# NSN 5935-01-113-7809

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-113-7809

Body Style:
Right angle type
Overall Length:
3.950 inches
Overall Height:
0.700 inches
Overall Width:
0.250 inches
Environmental Protection:
Vibration resistant and corrosion resistant and humidity resistant
Unthreaded Mounting Hole Diameter:
Between 0.090 inches and 0.098 inches
Distance Between Mounting Facility Centers:
3.700 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
900.0 single mating end single contact grouping
Polarization Method:
Inter-contact polarizing keys
Shell Type:
Solid
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2 military specification all treatment responses single mating end single contact grouping
Shell Material:
Aluminum alloy 380.0
Shell Surface Treatment:

Nickel

## NSN 5935-01-113-7809

Electrical Receptacle Connector - Page 2 of 2



#### **Shell Material Specification:**

Qq-a-591 federal specification single material response

### **Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end

### **Included Contact Quantity:**

64 single mating end single contact grouping

### **Included Contact Type:**

Round socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.064 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.