NSN 5935-01-113-8278

Cadmium

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-113-8278

Body Style: Angle shape w/cable clamp Overall Diameter: 1.031 inches Body Angle In Deg: 90.0 Environmental Protection: Moisture proof and salt water resistant and vibration proof Cable Entrance Diameter: Between 0.114 inches and 0.328 inches Mating End Quantity: 1
Overall Diameter: 1.031 inches Body Angle In Deg: 90.0 Environmental Protection: Moisture proof and salt water resistant and vibration proof Cable Entrance Diameter: Between 0.114 inches and 0.328 inches Mating End Quantity:
1.031 inches Body Angle In Deg: 90.0 Environmental Protection: Moisture proof and salt water resistant and vibration proof Cable Entrance Diameter: Between 0.114 inches and 0.328 inches Mating End Quantity:
Body Angle In Deg: 90.0 Environmental Protection: Moisture proof and salt water resistant and vibration proof Cable Entrance Diameter: Between 0.114 inches and 0.328 inches Mating End Quantity:
Environmental Protection: Moisture proof and salt water resistant and vibration proof Cable Entrance Diameter: Between 0.114 inches and 0.328 inches Mating End Quantity:
Environmental Protection: Moisture proof and salt water resistant and vibration proof Cable Entrance Diameter: Between 0.114 inches and 0.328 inches Mating End Quantity:
Moisture proof and salt water resistant and vibration proof Cable Entrance Diameter: Between 0.114 inches and 0.328 inches Mating End Quantity:
Cable Entrance Diameter: Between 0.114 inches and 0.328 inches Mating End Quantity:
Between 0.114 inches and 0.328 inches Mating End Quantity:
Mating End Quantity:
1
'
Contact Position Arrangement Style:
40515 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Connector Cable Strain Relief Method:
Cable clamp
Distance From Centerline To Connector End:
1.938 inches
Distance From Centerline To Cable End:
1.094 inches
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:

NSN 5935-01-113-8278

Electrical Plug Connector - Page 2 of 2



Shell	Surface	Treatment	Specification:
JIIEII	Juliace	HEAUHEIL	Specification.

Qq-p-416 federal specification single treatment response

Included Contact Quantity:

3 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.015 gold grains, troy and 0.015 silver grains, troy

Precious Material:

Gold and silver

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

96906-ms27500 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.