## NSN 5935-01-115-0783

**Thread Class:** 

Right-hand

**Thread Direction:** 

2a

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-115-0783

Body Style:
Straight shape, external coupling
Overall Length:
1.290 inches
Environmental Protection:
Moisture resistant and shock resistant and pressure proof
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thready Qty Per Inch (tpi):
28
Thread Size:
0.438 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Plastic polytetrafluoroethylene single mating end
Contact Surface Treatment Specification:
Qq-s-365 federal specification single treatment response single mating end single contact grouping
Terminal Type:
Turret single mating end single contact grouping

## NSN 5935-01-115-0783

A039b0

Electrical Receptacle Connector - Page 2 of 2

