

View Online at <https://aerobasegroup.com/nsn/5935-01-115-2584>

Body Style:

Straight shape

Overall Length:

0.780 inches

Overall Width:

0.210 inches

Environmental Protection:

Vibration resistant and moisture resistant and thermal shock resistant and salt water resistant

Unthreaded Mounting Hole Diameter:

0.094 inches

Distance Between Mounting Facility Centers:

0.565 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

9 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Mating end

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping or nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end or plastic polyphenylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 1st treatment response single mating end single contact grouping or qq-n-290, cl 2, type 7 federal specification 1st treatment response single mating end single contact grouping

Contact Material Specification:

Qq-c-533 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end or mil-p-46174, cl 40, grade e military specification single material response single mating end

Included Contact Quantity:

9 single mating end single contact grouping

Included Contact Type:

Twisted pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.