

View Online at <https://aerobasegroup.com/nsn/5935-01-115-4236>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

Between 1.305 inches and 1.353 inches

**Overall Diameter:**

Between 1.177 inches and 1.197 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

**Distance From Mounting Shoulder To Front Face:**

Between 0.894 inches and 0.906 inches

**Mounting Facility Thickness:**

0.125 inches

**Threaded Device Type:**

Back shell and mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

3-oct single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

68.0 and 178.0 and 204.0 and 247.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Thready Qty Per Inch (tpi):**

28 and 20

**Thread Size:**

0.625 inches and 0.750 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, cl 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy 6061

**Shell Surface Treatment:**

Chromium

**Shell Material Specification:**

Qq-a-367, t6 federal specification single material response

**Included Contact Quantity:**

3 single mating end single contact grouping

**Bushing Accommodation Hole Shape:**

Round w/flat

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.015 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Un and unef

**Specification Data:**

81349-mil-c-81511/49 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.