

View Online at <https://aerobasegroup.com/nsn/5935-01-115-5902>

**Thread Class:**

2a and 2b

**Thread Direction:**

Right-hand

**Body Style:**

Angle shape, pcb type

**Overall Length:**

1.850 inches

**Overall Height:**

0.655 inches

**Overall Width:**

0.390 inches

**Environmental Protection:**

Vibration resistant and shock resistant and salt spray proof and corrosion resistant and humidity resistant and thermal shock resistant

**Unthreaded Mounting Hole Diameter:**

0.120 inches

**Distance Between Mounting Facility Centers:**

1.600 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Jackscrew

**Shell Type:**

Solid

**Connector Locking Method:**

Jackscrew-socket

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 125.0 degrees celsius

**Thready Qty Per Inch (tpi):**

56

**Thread Size:**

0.086 inches

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic polyphenylene single mating end or plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type ii, grade c, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Solder stud single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

**Unable To Decode:**

Unable to decode and unable to decode

**Included Contact Quantity:**

20 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Special Features:**

Jackscrew type-female and location-right hand topandjackscrew type-male and location-left hand

**Precious Material And Location:**

Contact surf gold

**Precious Material And Weight:**

0.020 gold grains, troy

**Precious Material:**

Gold

**Supplementary Features:**

Mounting method - unthreaded hole

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.