Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-115-7286

Body Style:

Straight shape

Overall Length:

1.480 inches

Overall Height:

0.865 inches

Overall Width:

0.208 inches

Environmental Protection:

Corrosion resistant and dust resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.089 inches and 0.094 inches

Distance Between Mounting Facility Centers:

1.270 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type i, gr c or d optional, class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-b-626, alloy 260, hard federal specification single material response single mating end single contact grouping



S	hell Material:
A	luminum alloy
S	hell Surface Treatment:
Ν	ickel
S	hell Surface Treatment Specification:
Μ	il-c-26074, class 3, gr a military specification single treatment response
S	hell Material Specification:
Q	q-a-591, alloy a380 federal specification single material response
In	sert Material Specification:
Μ	il-m-14, type sdg-f military specification single material response single mating end
In	cluded Contact Quantity:
37	7 single mating end single contact grouping
In	cluded Contact Type:
R	ound socket single mating end single contact grouping
P	recious Material And Location:
С	ontact surfaces gold
P	recious Material And Weight:
0.	037 gold grains, troy
P	recious Material:
G	old
S	helf Life:
N	/a
U	nit Of Measure:
D	emilitarization:
Ν	0
Fi	iig:
A	039b0
Μ	il-std (military Standard):
	il-g-45204 spec.