

View Online at <https://aerobasegroup.com/nsn/5935-01-115-8570>

**Thread Class:**

2a and 2a and 2a

**Thread Direction:**

Left-hand and right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.375 inches

**Overall Diameter:**

1.733 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof and shock resistant and cold resistant and heat resistant and explosion proof

**Distance From Mounting Shoulder To Front Face:**

0.906 inches

**Mounting Facility Thickness:**

Between 0.094 inches and 0.200 inches

**Threaded Device Type:**

Back shell and coupling facility and mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

16s-1 single mating end

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thready Qty Per Inch (tpi):**

20 and 10 and 18

**Thread Size:**

0.875 inches and 1.000 inches and 1.125 inches

**Insert Material:**

Rubber single mating end

**Shell Material:**

Stainless steel

**Bushing Accommodation Hole Shape:**

Round

**Special Features:**

16-1 insert configuration

**Thread Series Designator:**

Unef and double stub and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0