

View Online at <https://aerobasegroup.com/nsn/5935-01-115-8570>

Thread Class:

2a and 2a and 2a

Thread Direction:

Left-hand and right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.375 inches

Overall Diameter:

1.733 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and shock resistant and cold resistant and heat resistant and explosion proof

Distance From Mounting Shoulder To Front Face:

0.906 inches

Mounting Facility Thickness:

Between 0.094 inches and 0.200 inches

Threaded Device Type:

Back shell and coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

16s-1 single mating end

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

20 and 10 and 18

Thread Size:

0.875 inches and 1.000 inches and 1.125 inches

Insert Material:

Rubber single mating end

Shell Material:

Stainless steel

Bushing Accommodation Hole Shape:

Round

Special Features:

16-1 insert configuration

Thread Series Designator:

Unef and double stub and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0