

View Online at <https://aerobasegroup.com/nsn/5935-01-115-8576>

Thread Class:

2a and 2a and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.907 inches

Overall Diameter:

Between 2.615 inches and 2.635 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and shock resistant and cold resistant and heat resistant and explosion proof

Distance From Mounting Shoulder To Front Face:

Between 1.162 inches and 1.182 inches

Mounting Facility Thickness:

Between 0.094 inches and 0.203 inches

Threaded Device Type:

Back shell and coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

32-8 single mating end

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Operating Temperature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thready Qty Per Inch (tpi):

16 and 10 and 16

Thread Size:

1.875 inches and 2.000 inches and 2.125 inches

Insert Material:

Rubber single mating end

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

Shell Material Specification:

Qq-s-763 federal specification single material response

Bushing Accommodation Hole Shape:

Round

Unable To Decode:

Unable to decodeunable to decode

Thread Series Designator:

Un and double stub and un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0