

View Online at <https://aerobasegroup.com/nsn/5935-01-115-8874>

**Body Style:**

Straight shape w/flange

**Overall Length:**

1.406 inches

**Overall Height:**

1.453 inches

**Overall Width:**

1.453 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

**Unthreaded Mounting Hole Diameter:**

0.120 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.156 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.156 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.688 inches and 0.719 inches

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

20-41 all mating ends

**Contact Removability:**

Nonremovable all mating ends single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

600.0 all mating ends single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

126.0 and 234.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Contact Surface Treatment:**

Gold all mating ends single contact grouping and nickel all mating ends single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, cl 1, grade c military specification 1st treatment response all mating ends single contact grouping and qq-n-290, grade e federal specification 2nd treatment response all mating ends single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Shell Material Specification:**

Qq-a-591 federal specification single material response

**Included Contact Quantity:**

41 1st mating end single contact grouping

**Included Contact Type:**

Round socket 2nd mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.082 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

96906-ms3119 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.